

# Product data sheet

## Powerturn F-IS

Electro-mechanical swing door drive system for 2-leaf fire and smoke protection doors with closing sequence control



### Product features

Smart swing function for easy manual door opening
Closing force of EN4-7 with variable adjustment
Opening and closing speed can be individually adjusted
Mechanical latching action when operated without current, and electrical latching action in regular operation, which accelerates the door shortly before the closed position
Mechanical and electrical closing sequence control holds the active leaf in the waiting position until the passive leaf is closed
Low-energy function opens and closes the door with reduced speed, fulfilling the highest safety requirements
Vestibule function controls the opening and closing of two consecutive doors (interlocking door system)
Obstacle detection detects obstacles through contact and stops the opening or closing process
Automatic reversing detects an obstacle and returns to the opening position
Push & Go function triggers the automatic drive components following light manual pressure on the door leaf
Drive can be used with roller guide rail or link arm
Servo function for motorized support when manually opening the door
Optional radio board for wireless activation by radio transmitter

### Application Areas

Fire and smoke protection doors
Double leaf right and left single-action doors
Single-action doors up to 3200 mm hinge clearance, 1600 mm leaf width and 600 kg weight
Minimum hinge clearance 1600 mm
Interior and exterior doors with high access frequency
Transom installation hinge and opposite hinge side

### Product Data Table

Product features	Powerturn F-IS
Reveal depth (max.)*	300 mm
Door opening angle (max.)*	136 °
DIN left	Yes
DIN right	Yes
Transom installation opposite hinge side with link arm	Yes
Transom installation opposite hinge side with roller guide rail	Yes
Transom installation hinge side with roller guide rail	Yes

Mechanical latching action	Yes
Electrical latching action	Yes
Electrical closing sequence control	Yes
Mechanical closing sequence control	Yes
Disconnection from mains	Main switch in the drive
Power supply for external consumers (24 V DC)	1.2 A
Modes of operation	Automatic, Off, Permanently open, Shop closing, Night
Automatic function	Yes
Low-energy function	Yes
function smart swing	Yes
Servo function	Yes
Obstacle detection	Yes
Automatic reversing	Yes
Push & Go	adjustable
Operation	Programme switch DPS, Programme switch integrated in the drive, Programme switch MPS
For fire resistance doors	Yes

### Accessory

#### Product name

Powerturn 230 V T-distributor  
 GC 338  
 GC 342  
 Integrated opening restrictor  
 Spindle extension Powerturn  
 Adaptor for sensor link arm

### Part

#### Product name

GC GR for GC 338 Powerturn  
 GEZE Powerturn F-IS  
 Link arms Powerturn / Powerturn F  
 Cover Powerturn  
 Powerturn / Powerturn F roller guide rail  
 Connection - 230 V  
 GEZE Powerturn F  
 Installation kit for mechanism for integrated closing sequence control