

Product data sheet

TS 1500 with hold-open arm

Overhead door closer with link arm for single-leaf doors with a leaf width up to 1100 mm



Product features

Variable closing force of EN3 or EN4 by reversing the bearing block
Can be used for right and left hand doors without conversion
Mechanical hold-open unit through hold-open linkage with hold-open area 70°-150°
Hydraulic latching action which accelerates the door shortly before the closed position
Closing speed can be individually adjusted

Application Areas

Right and left single-action doors
Holds doors without smoke and fire protection requirements open
Single-action doors up to 1100 mm leaf width
Door leaf installation hinge side and transom installation opposite hinge side
Door leaf installation opposite hinge side possible in parallel arm installation

Product Data Table

Product features	TS 1500 with hold-open arm
Closing force in accordance with EN 1154	EN 3/4
Recommended leaf width up to	1100 mm
Type of installation	Door leaf installation hinge side, Door leaf installation opposite hinge side, Transom installation opposite hinge side
Door opening angle (max.)*	180 °
Closing force adjustable	Yes, via installation
Adjustable closing speed	Yes
Latching action adjustable	Yes, via link arm
Hold-open angle	70 ° - 150 °

Accessory

Product name

Link arms TS 4000/2000 / F
Link arms TS 4000/2000 / F