

### Product data sheet

## **OL 95**

Surface-mounted slimline skylight opener with an opening width of 220 mm





## Product data sheet OL 95

2/3

#### **Product features**

Achieves the full opening width of 220 mm for all leaf heights

The opening width can be set

Low space requirement thanks to flat design of the scissor stays

Integrated leaf locking mechanism in the scissor stays guarantees safe locking

Unhinging inhibitor and lockable hand lever offer an additional safety

The additional lock increases safety and air-tightness

Scissor disengagement by pressing the release button facilitates window cleaning from inside and outside

Completely pre-mounted assembly groups facilitate installation

#### **Application Areas**

Comfortable and daily ventilation of rooms and staircases
Inward-opening bottom hung windows
Special forms such as pitched and triangular windows possible
Installation on wooden, PVC or light alloy windows
Frame installation

#### **Product Data Table**

Productname	OL 95
Length	305 mm
Opening width	220 mm
Leaf width (min.)	440 mm
Min. leaf height	350 mm
Leaf weight (max.)	60 kg
Fitting stroke	54 mm
Adjustable opening width (stroke reduction)	Yes
Leaf lock integrated in the scissor stay	Yes
Scissor stay unhooked by release button	Yes
Lockable	Yes
Unhinging inhibitor	Yes



# Product data sheet OL 95

3/3

#### Accessory

#### **Product name**

Gripping and cleaning scissor stay (FPS)